



5Y3-GT

5Y3-GT
ET-T965
 Page 1
 10-55

TWIN DIODE

FOR FULL-WAVE POWER RECTIFIER APPLICATIONS

DESCRIPTION AND RATING

The 5Y3-GT is a filamentary twin-diode designed for full-wave rectifier operation in power supplies that have d-c output current requirements up to approximately 125 milliamperes.

GENERAL

ELECTRICAL

Cathode—Coated Filament
 Filament Voltage, AC or DC 5.0 Volts
 Filament Current 2.0 Amperes

MECHANICAL


Mounting Position—Vertical*
 Envelope—T-9, Glass
 Base—B5-10, Intermediate Shell Octal 5-Pin
 or B5-62, Short Intermediate Shell Octal 5-Pin

MAXIMUM RATINGS

RECTIFIER SERVICE—DESIGN-CENTER VALUES†

Peak Inverse Plate Voltage 1400 Volts
 AC Plate-Supply Voltage per Plate—See Rating Chart †‡
 Steady-State Peak Plate Current per Plate 440 Milliamperes
 Transient Peak Plate Current per Plate, Maximum Duration 0.2
 Second 2.5 Amperes
 DC Output Current—See Rating Chart †‡


BASING DIAGRAM



TERMINAL CONNECTIONS

- Pin 1—No Connection
- Pin 2—Filament
- Pin 4—Plate Number 2
- Pin 6—Plate Number 1
- Pin 8—Filament

PHYSICAL DIMENSIONS



RETMA 9-13 OR 9-42



Supersedes ET-T250B, dated 6-50

CHARACTERISTICS AND TYPICAL OPERATION

FULL-WAVE RECTIFIER


	Capacitor- Input Filter	Choke Input Filter
AC Plate-Supply Voltage per Plate, RMS.....	350	500 Volts
Filter Input Capacitor.....	20	... Microfarads
Filter Input Choke.....	...	10 Henrys
Total Plate-Supply Resistance per Plate.....	50	... Ohms
DC Output Current.....	125	125 Milliampers
DC Output Voltage at Filter Input.....	360	380 Volts
 Tube Voltage Drop		
$I_b = 125$ Milliampers DC per Plate.....	50	Volts

* Horizontal operation is permitted if pins 2 and 4 are in a vertical plane.


† To simplify the application of the maximum ratings to circuit design, the electrical design-center maximum ratings are also presented in chart form as Rating Charts I, II, and III. Rating Chart I presents the maximum ratings for a-c plate supply voltage and d-c output current. Rating Chart II provides a convenient method for checking conformance with the maximum steady-state peak-plate-current rating. Rating Chart III offers a convenient method for checking conformance with the maximum transient peak-plate-current rating.
 With a capacitor-input filter, the conditions of each of Rating Charts I, II, and III must be satisfied; with a choke-input filter, operation must be within the indicated boundary of Rating Chart I.

‡ The maximum ratings for a-c plate supply voltage and d-c output current are interrelated and are also dependent on whether a choke- or capacitor-input filter is employed. This relationship is shown in Rating Chart I. With a capacitor-input filter, the operating point of d-c output current and a-c supply voltage must fall within the curve FAEDG. With a choke-input filter, the operating point must fall within the curve FABCDG.


Note: The indicated values of a-c plate supply voltage shown throughout the data are measured without load.




RATING CHART II




RATING CHART III



OPERATION CHARACTERISTICS
 FULL-WAVE RECTIFIER WITH CHOKE-INPUT FILTER



OPERATION CHARACTERISTICS
 FULL-WAVE RECTIFIER WITH CAPACITOR-INPUT FILTER



AVERAGE PLATE CHARACTERISTICS

EACH SECTION

