

Beam Power Tube

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	6.3	volts
Current	0.45 ± 6%	amp
Warm-up time (Average)	11	sec

Direct Interelectrode Capacitances:[▲]

Grid No.1 to plate	0.4 max.	μf
Grid No.1 to cathode & grid No.3, grid No.2, and heater	9	μf
Plate to cathode & grid No.3, grid No.2, and heater	6	μf


Characteristics, Class A₁ Amplifier:

Plate Voltage	75	250	volts
Grid-No.2 Voltage	250	250	volts
Grid-No.1 Voltage	0	-15	volts ←
Plate Resistance (Approx.)	-	73000	ohms
Transconductance	-	4800	μmhos
Plate Current	130 [●]	46	ma
Grid-No.2 Current	16 [●]	4.6	ma
Grid-No.1 Voltage (Approx.) for plate μa = 100	-	-40	volts ←

Mechanical:

Operating Position	Any
Maximum Overall Length	3-1/16"
Maximum Seated Length	2-13/16"
Length, Base Seat to Bulb Top (Excluding tip)	2-7/16" ± 3/32"
Maximum Diameter	0.750" to 0.875"
Dimensional Outline	See <i>General Section</i>
Bulb	T6-1/2
Base	Small-Button Noval 9-Pin (JEDEC No. E9-1)
Basing Designation for BOTTOM VIEW	9HN

Pin 1 - Grid No.2
 Pin 2 - No Connection
 Pin 3 - Grid No.1
 Pin 4 - Heater
 Pin 5 - Heater
 Pin 6 - Grid No.1



Pin 7 - Cathode,
 Grid No.3
 Pin 8 - Internal
 Connection—
 Do Not Use
 Pin 9 - Plate

← Indicates a change.



6CZ5

VERTICAL-DEFLECTION AMPLIFIER

→ Maximum Ratings, Design-Maximum Values:

*For operation in a 525-line, 30-frame system**

DC PLATE VOLTAGE.	350	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE [♦]	2200	max.	volts
DC GRID-No.2 (SCREEN-GRID) VOLTAGE.	315	max.	volts
PEAK NEGATIVE-PULSE GRID-No.1 (CONTROL-GRID) VOLTAGE.	275	max.	volts
CATHODE CURRENT:			
Peak.	155	max.	ma
Average	45	max.	ma
GRID-No.2 INPUT	2.2	max.	watts
PLATE DISSIPATION	10	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200 [♣]	max.	volts
BULB TEMPERATURE (At hottest point on bulb surface).	250	max.	°C

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:


For fixed-bias operation.	0.5	max.	megohm
For cathode-bias operation.	1	max.	megohm

- ▲ Without external shield.
- This value can be measured by a method involving a recurrent wave form such that the maximum ratings of the tube will not be exceeded.
- ★ As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.
- ♦ This rating is applicable when the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.
- ♣ The dc component must not exceed 100 volts.

→ Indicates a change.



AVERAGE PLATE CHARACTERISTICS



92CM-9155




6CZ5

AVERAGE CHARACTERISTICS

$E_f = 6.3$ VOLTS


GRID-No 2 VOLTS = 250



92CM-9157



AVERAGE CHARACTERISTICS



92CM-9156R1

